



## PRODUCT DATASHEET

PR-M12-3040K

### PRODUCT DESCRIPTION:

#### PURERENA LED Module Features:

- Modular and adjustable recessed LED luminaires
- Ideal for lighting walls
- Housing made of extruded aluminum
- High performance heatsink to minimize light decline
- 2 CCT (3000K + 4000K)



### PICTURES:



### LED MODULE 12W - 2 CCT



### SCOPE OF APPLICATION:

Widely used in factory workshops, warehouses, pharmaceuticals, textiles, dyeing and other industrial sites.

### SPECIFICATIONS:

Nominal Wattage	12W
LED Chip	PHILIPS Chip
Nominal Voltage	AC220-240V
Main's Frequency	50/60 Hz
DF	≥0.9
Color Temperature	2 CCT (3000K + 4000K)
CRI	RA ≥90
Switching Cycles	15,000
Driver Brand	Isolated
Size (mm)	ø60*H68mm
Trim Color	Black
Body Materials	Aluminium

Temperature Range	-20 to +55 °C
Lifespan	50,000 Hrs.
Mounting Type	Recessed
Mounting Location	With down light housing
Dimmable	No
Current	250mA
IP Rating	IP20
Lumens Efficiency	100lm/W
Total Lumin	1200lm
Warranty	5 Years