

PRODUCT DATASHEET

LED EMERGENCY DRIVER 3-60W

PRODUCT DESCRIPTION:

PURERENA EM CONVERTER LED BASIC

- LED Emergency driver
- Model: PR-FD-F1A
- Input voltage: AC265V
- Material: ABS+Aluminum
- Size: 110*55*21mm
- Battery: li-ion18650 3. 7V 2400mAH/3500mAH
- Emergency power: 4W
- Emergency time: 2hrs / 3hrs



PICTURES:



DIMENSIONS:

110 X 55 X 21mm

TECHNICAL SPECIFICATIONS:

Input Voltage	AC265V~50/60Hz
Output Voltage	230V
Power for	3 - 60W
Materials	ABS + Aluminum
Size	110*55*21mm
Battery Type	li-ion 18650 11.1 V 2400mAH/3500mAH
Emergency Power	4W
Emergency Time	120min
Certificates	CE / Rohs
Application	3-60W LED light ,LED Tube
Operation Type	Non maintained operation
Rated Duration	1 Hrs / 3 Hrs
Duration Link	Operating time selectable with plug

PRODUCT DATASHEET

LED EMERGENCY DRIVER 3-60W

PROPERTIES:

- Non maintained operation
- 1 or 3 h rated duration
- Operating time selectable with plug (duration link)
- Compatible with all dimmable and non-dimmable constant current LED Driver
- 3-pole technology: 2-pole LED module changeover and delayed power switching for the LED Driver
- Automatic shutdown of output if LED load is out of range
- Constant power output
- Maximum light output for all LED modules
- Electronic charge system
- Deep discharge protection
- Short-circuit-proof battery connection
- Polarity reversal protection for battery

BATTERY PROPERTIES:

- High-temperature cells
- LA or 18650 cells
- 4-year design life for NiMH batteries
- 1-year guarantee for NiMH batteries
- 2 - 4 years design life for batteries
- 2-year guarantee for LiFePO4 batteries