

## PRODUCT DATASHEET

### PRODUCT DESCRIPTION:

#### PURERENA LED Strip Light SMD Features:

- High light transmittance.
- Good protective performance.
- Good flexibility, and high substitutability.
- Outstanding weather & UV resistance.



### PICTURES:



### LED STRIP LIGHT SMD IP65



### SCOPE OF APPLICATION:

General indoor illumination, general outdoor illumination decorative illumination, and private living areas.

### SPECIFICATIONS:

|                    |                       |
|--------------------|-----------------------|
| Color              | Transparent           |
| LED Chip           | HongLi                |
| Working Voltage    | DC24V                 |
| Rated Power / M    | 4W/10W/14.4W          |
| LED Qty/ M         | 480 LEDs              |
| Color Temperature  | 2700K / 3000K / 4000K |
| CRI                | RA ≥90                |
| Lumen              | 80LM/W±10%@4000K      |
| PCB Size           | 8mm / 10mm            |
| Max Running Length | 5M                    |
| Cutting Length     | 5 CM (1 Unit)         |
| Packing            | 5M Roll               |

|                     |                        |
|---------------------|------------------------|
| Storing Temp.       | -40 ~ 60 °C            |
| Lifespan            | 50,000 Hrs.            |
| 2 PIN Connector     | Included (1 PC)        |
| Water Proof End Cap | Included (1 PC)        |
| Front Cap with Wire | Included (1 PC)        |
| Silicon Glue        | Included (1 PC - 10ml) |
| IP Rating           | IP65                   |
| Extrusion Material  | High Grade Silicon     |
| Origin              | China                  |
| Warranty            | 5 Years                |


**PRODUCT DATASHEET**

**LED STRIP LIGHT SMD  
IP65**


**PRODUCT MODELS:**

| Model Number           | Voltage | Wattage/M | Lumen/M | CCT   | CRI   | Cutting Unit |
|------------------------|---------|-----------|---------|-------|-------|--------------|
| PR-STR4-SMD27-IP65-5M  | DC24V   | 4W        | 100LM/W | 2700K | RA>90 | 5 CM         |
| PR-STR4-SMD30-IP65-5M  | DC24V   | 4W        | 100LM/W | 3000K | RA>90 | 5 CM         |
| PR-STR4-SMD40-IP65-5M  | DC24V   | 4W        | 100LM/W | 4000K | RA>90 | 5 CM         |
| PR-STR10-SMD27-IP65-5M | DC24V   | 10W       | 100LM/W | 2700K | RA>90 | 5 CM         |
| PR-STR10-SMD30-IP65-5M | DC24V   | 10W       | 100LM/W | 3000K | RA>90 | 5 CM         |
| PR-STR10-SMD40-IP65-5M | DC24V   | 10W       | 100LM/W | 4000K | RA>90 | 5 CM         |
| PR-STR14-SMD27-IP65-5M | DC24V   | 14.4W     | 100LM/W | 2700K | RA>90 | 5 CM         |
| PR-STR14-SMD30-IP65-5M | DC24V   | 14.4W     | 100LM/W | 3000K | RA>90 | 5 CM         |
| PR-STR14-SMD40-IP65-5M | DC24V   | 14.4W     | 100LM/W | 4000K | RA>90 | 5 CM         |



**PRODUCT SIZE:**



• Section diagram




• Bending diameter



#### PHOTOELECTRIC PARAMETERS:

#### • Colour Temperature Chart




2200K

4000K

6500K

4000K

2200K



#### • Lux Chart

光通输出:929.7 lm

