

### WATER PROOF LED DRIVER 24V - 60W IP67 | Water Proof Series

#### PRODUCT DESCRIPTION:

- Moisture Proof, Mildew Proof, and Salt Fog Proof.
- Full Glue-filled Design.
- Adopt Active PFC Circuit.
- IP67 Protection.
- 3 Years Warranty.



#### PICTURES:



#### SIZE:



#### SPECIFICATIONS:

FEATURES	
INPUT VOLTAGE	220-240V~ 50/60HZ
EFFICIENCY	87% min@230Vac full load
RATED POWER	60W
LIGHTNING SURGE	Differential Model+/-0.5KV(2 ohm)
HI-POT	1500Vac for 60 seconds
PROTECTION	Over-temperature drop-voltage protection
IP RATING	IP67
DIMENSION	102 x 47.5 x 24.5(mm)
WARRANTY	3 Years

**WATER PROOF LED DRIVER 24V - 60W**  
IP67 | Water Proof Series

**SPECIFICATIONS:**

**ELECTRICAL SPECIFICATIONS**

EFFICIENCY	87%
OUTPUT VOLTAGE	DC24V
RATED CURRENT	2.5A
INPUT MAX CURRENT	0.65A @180Vac full load
COLD START CURRENT	40A/230VAC
POWER FACTOR	PF $\geq$ 0.6
CURRENT RANGE	0~2.5A

**PROTECTION**

SHORT CIRCUIT	Hiccup Mode, recovers automatically after fault condition is removed
OVER CURRENT	Protection mode; the product is hiccup state, protect the product from damage, when the fault is ruled out, the power supply is normal
OVERVOLTAGE PROTECTION	Protection mode; the product is hiccup state, protect the product from damage, when the fault is ruled out, the power supply is normal

**ENVIROMENT, SAFETY & EMC**

WORKING TEMP.	-25 ~ +35°C
MAX ENCLOSURE TEMP.	T case=+78°C
WORKING HUMIDITY	20 ~ 95% RH Non-condensing
STORAGE TEMP, HUMIDITY	-30 ~ +80°C , 10 ~ 95% RH